

Prévio Gama PR 100



Rating: Not Rated Yet
[Ask a question about this product](#)

Description

Posibilidad de alimentación directa 5V por el receptor TDT

Amplificadores de bajo ruido

REF.	PR-100	PR-101
ENTRADAS ENTRÉES INPUTS ENTRADAS	1 BIII/UHF	1 UHF
BANDA COBERTA BANDE COUVERTE BAND RANGE BANDA CUBIERTA	MHz 170-860	470-860
GANHO GAIN GANANCIA	dB 15	
NÍVEL MÁXIMO SALIDA NIVEAU MAXIMUM SORTIE MAXIMUM OUTPUT LEVEL NÍVEL MÁXIMO SALIDA	dBµV 96*	93**
FACTOR DE RUIDO FACTEUR DE BRUIT NOISE FIGURE FACTOR RUIDO	dB <2	
CONSUMO CONSOMMATION CONSUMPTION CONSUMACION	mA 10	
ALIMENTACIÓN SUPPLY ALIMENTACION	VDC 5...24V ---	
CONEXÃO CONNECTEURS CONNECTION CONEXION	Fichas tipo "F" Fiches type "F" "F" Connectors Conectores tipo "F"	

PR-101

UHF

*DIN 45008, IM03- 60dB, 3P

**EN 50002-3, IM03- 60dB, 2P